

CATV/SAT Splitters


NE210XS Series CATV Splitters(5~1000MHz)

FEATURES


- Zinc die cast housing, bright tin finished and solder shield bottom plate.
- All ports are F-(f) connectors, 75 ohm.
- Grounding terminal provided.
- Two pieces of screws attached.
- High RFI product, RFI>110dB
- Light weight and compact size.



NE2102S



NE2103S



NE2104S

SPECIFICATIONS

Item	Frequency	NE2102S	NE2103S	NE2104S
Insertion Loss IN-OUT (max. dB)	5-40MHz	3.5	5.5	7.0
	40-470MHz	3.6	5.8	7.2
	470-750Mhz	3.8	6.0	7.5
	750-860Mhz	4.0	6.4	7.9
	860-1000MHz	4.2	6.7	8.5
Mutual Isolation OUT-IN (min. dB)	5-40MHz	32	30	30
	40-470MHz	30	28	28
	470-750Mhz	30	28	28
	750-860Mhz	30	28	28
	860-1000MHz	28	26	26
Return Loss IN/OUT (min. dB)	5-40MHz	22	22	22
	40-470MHz	22	20	20
	470-750Mhz	20	20	20
	750-860Mhz	20	18	18
	860-1000MHz	20	18	18